



US006584814B2

(12) **United States Patent**  
Son et al.

(10) **Patent No.:** US 6,584,814 B2  
(45) **Date of Patent:** Jul. 1, 2003

(54) **WASHING MACHINE WITH TILTED WASHING TUB**

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2,583,823 A	*	1/1952	Dunham	68/25
4,526,020 A		7/1985	Fey et al.	
5,090,220 A		2/1992	Fukuzawa et al.	
5,661,914 A		9/1997	Millet	

\* cited by examiner

(75) **Inventors:** JI Chang Son, Kyungsangnam-do (KR); Hye Yong Park, Kyungsangnam-do (KR); Bong Sang Lee, Kyungsangnam-do (KR); Chang Won Ryu, Kyungsangnam-do (KR)

(73) **Assignee:** LG Electronics, Inc., Seoul (KR)

(\*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 82 days.

**Primary Examiner**—Philip R. Coe

(74) **Attorney, Agent, or Firm**—Birch, Stewart, Kolasch & Birch, LLP

(21) **Appl. No.:** 09/837,385

(22) **Filed:** Apr. 19, 2001

(65) **Prior Publication Data**

US 2002/0002847 A1 Jan. 10, 2002

(30) **Foreign Application Priority Data**

Apr. 19, 2000 (KR) ..... 2000-20736

(51) **Int. Cl.<sup>7</sup>** ..... D06F 23/06; D06F 37/26

(52) **U.S. Cl.** ..... 68/24; 68/3 R

(58) **Field of Search** ..... 68/3 R, 23.2, 24, 68/25, 146

(57) **ABSTRACT**

Disclosed herein is a washing machine with a tilted washing tub. The washing machine includes a casing on the rear portion of which an opening is formed. The opening is covered with a rear cover provided with an outward protrusion. A washing tub consists of outer and inner tubs. The outer tub is positioned in the casing to be tilted forward at a predetermined angle for containing washing water. The inner tub is positioned in the outer tub for washing and spin-drying laundry. Drive means is positioned under the outer tub to rotate the outer tub.

**20 Claims, 5 Drawing Sheets**

